

www.CHOOCHOOPARTS.com



PRODUCT NAME	Pro Zoom® 60	Pro Zoom® 54	Pro Zoom® 52 Stand-On	Max Zoom® 60	Max Zoom® 52	Max Zoom® 48
MODEL NUMBER	992807	992806	994806	991087	991086	991085
ENGINE	Kawasaki® FX	Kawasaki® FX	Kawasaki® FX	Kawasaki® FR Twin	Kawasaki® FR Twin	Kawasaki® FR Twin
HORSEPOWER*	27 hp	27 hp	20 hp	26 hp	24 hp	24 hp
DISPLACEMENT (cc)	852 cc	852 cc	603 cc	726 cc	726 cc	726 cc
DRIVE SYSTEM	Hydrostatic Hydro-Gear® 16cc Pump with Parker® 17.4 c.i. Wheel Motors	Hydrostatic Hydro-Gear® 16cc Pump with Parker® 17.4 c.i. Wheel Motors	Pumps and Motors 10 CC	Hydro-Gear® ZT-3100 Transaxles	Hydro-Gear® ZT-3100 Transaxles	Hydro-Gear® ZT-3100 Transaxles
FUEL CAPACITY Gallons (Liters)	13.4 Gallons (50.7L)	13.4 Gallons (50.7L)	6 Gallons (22.7 L)	7.3 Gallons (27.6L)	7.3 Gallons (27.6L)	7.3 Gallons (27.6L)
GROUND SPEED (APPROX. MPH) (FORWARD/REVERSE)	13 mph/5 mph	13 mph/5 mph	9 mph / 4.5 mph	8 mph/4 mph	8 mph/4 mph	8 mph/4 mph
STARTER	Electric	Electric	Electric	Electric	Electric	Electric
DECK						
DECK MATERIAL	7 ga Steel with .25" Spindle Reinforcement	7 ga Steel with .25" Spindle Reinforcement	7 ga	10 ga w/ .25" Spindle Reinforcement	10 ga w/ .25" Spindle Reinforcement	10 ga w/ .25" Spindle Reinforcement
DECK CONSTRUCTION	Welded	Welded	Welded	Welded	Welded	Welded
NUMBER OF SPINDLES	3	3	3	3	3	3
BLADE TIP SPEED (FPM)	18,500	18,500	18,246	18,000	18,000	18,000
SPINDLE MATERIAL	Cast Iron	Cast Iron	Aluminum	Cast Iron	Cast Iron	Cast Iron
SPINDLE SHAFT	1" Steel	1" Steel	1" Steel	Steel	Steel	Steel
SPINDLE BEARINGS	Tapered Bearing	Tapered Bearing	1" Sealed	Ball Bearing	Ball Bearing	Ball Bearing
DECK DRIVE	Belt	Belt	Belt	Belt	Belt	Belt
DECK ENGAGEMENT	Ogura® GT 3.5 Electric Clutch	Ogura® GT 3.5 Electric Clutch	Electric Ogura® GT1A	Electric Ogura® GT1A	Electric Ogura® GT1A	Electric Ogura® GT1A
DECK LIFT SYSTEM	Foot Operated	Foot Operated	Manual	Adjustable Foot Operated	Adjustable Foot Operated	Adjustable Foot Operated
CUTTING WIDTH	60"	54"	52	60"	52"	48"
CUTTING HEIGHTS	1" - 6"	1" - 6"	1.5" - 4.5"	1"- 5"	1"- 5"	1"- 5"
CUTTING POSITIONS	21	21	7	9	9	9
WHEELS						
FRONT AXLE	Pivoting/Locking	Pivoting/Locking	Rigid	Fixed	Fixed	Fixed
FRONT	Smooth 13" x 6"- 6"	Smooth 13" x 6"- 6"	11" x 4"- 5"	Smooth 13" x 5"- 6"	Smooth 13" x 5"- 6"	Smooth 13" x 5"- 6"
REAR	Turf 24" x 12" - 12"	Turf 24" x 12" - 12"	18" x 8.5"-8"	Turf 20" x 10"- 10"	Turf 20" x 10"- 10"	Turf 20" x 10"- 10"
FEATURES						
HOOD	N/A	N/A	N/A	N/A	N/A	N/A
HEADLIGHTS	N/A	N/A	N/A	Optional	Optional	Optional
SEAT	High Back w/ Full Suspension & Arm Rests	High Back w/ Full Suspension & Arm Rests	N/A	High Back w/ Seat Springs & Arm Rests	High Back w/ Seat Springs & Arm Rests	High Back w/ Seat Springs & Arm Rests
HOUR METER	Standard	Standard	Standard	Standard	Standard	Standard
DIMENSIONS				•	·	
WEIGHT (LBS)	1201	1173	860	853	832	823
LENGTH	80.5"	80.5"	58"	74.5"	74.5"	71.5"
WIDTH	75" w/chute 61" w/o chute	70" w/chute 55" w/o chute	52.5"	62.8" (w/o chute)	55.5" (w/o chute)	50" (w/o chute)
HEIGHT	74" w/rops up 49" w/rops down	74" w/rops up 49" w/rops down	47.5"	42"	42"	42"
WARRANTY						
MACHINE	2 Year Limited Commercial		3 Year Limited Consumer, 1 Year Limited Commercial			
DECK SHELL & FRAME	Limited Lifetime		5 Year Limited			
SPINDLES	2 Year Limited		3 Year Limited			
ATTACHMENTS & ACCESSORIES	MENTS & ACCESSORIES					
OPTIONAL	3 Bucket Bagger, Weight Kit Mulching Kit, Grass Collector		3-Bucket Powered Bagger Kit, Mulching Kit, Trailer Hitch Kit, 36" Poly Roller, 48" Aerator, 48" Dethatcher, 15-Gallon Sprayer, Spreader, Dump Cart, Wheel Covers, Headlight Kit, Suspension Seat Kit, Lawn Striping Kit, Discharge Cover Kit, Engine Guard, FlexTend™ Shoulder Support System, Operator Controlled Chute Baffle, Seat Cover, Mower Cover			

Zoom XL® 54	Zoom XL® 48	Zoom XL® 42	Zoom® 50	Zoom® 42	Zoom® 34
915167	915165	915163	915161	915159	915157
Kawasaki® FR Twin	Kawasaki® FR Twin	Kawasaki® FR Twin	Kohler® Courage Twin	Kohler® Courage Twin	Briggs & Stratton® Single Cylinder
24 hp	24 hp	22 hp	25 hp	22 hp	14.5 hp
726 cc	726 cc	726 cc	725 cc	725 cc	500 cc
Hydro-Gear® ZT-2800 Transaxles	Hydro-Gear® ZT-2800 Transaxles	Hydro-Gear® ZT-2800 Transaxles	Hydro-Gear® EZT Transaxles with 1" Axle Shafts	Hydro-Gear® EZT Transaxles with 1" Axle Shafts	Hydro-Gear® EZT Transaxles with 1" Axle Shafts
3.8 Gallons (14.4L)	3.8 Gallons (14.4L)	3.8 Gallons (14.4L)	2.5 Gallons (9.5L)	2.5 Gallons (9.5L)	2.5 Gallons (9.5L)
6.5 mph /3 mph	6.5 mph /3 mph	6.5 mph /3 mph	6 mph/3 mph	6 mph/3 mph	6 mph/3 mph
Electric	Electric	Electric	Electric	Electric	Electric
10 ga w/ Doubler Plate	10 ga w/ Doubler Plate	10 ga w/ Doubler Plate	12 ga	12 ga	12 ga
Welded	Welded	Welded	Stamped	Stamped	Stamped
3	3	3	3	3	2
16,950	16,800	17,000	17,800	17,000	17,500
Aluminum	Aluminum	Aluminum	Steel	Steel	Steel
1" Steel	1" Steel	1" Steel	Steel	Steel	Steel
1" Sealed	1" Sealed	1" Sealed	Sealed	Sealed	Sealed
Belt	Belt	Belt	Belt	Belt	Belt
Electric Warner®	Electric Warner®	Electric Warner®	Electric Warner®	Electric Warner®	Electric Warner®
Foot Operated	Foot Operated	Foot Operated	Foot Operated	Foot Operated	Foot Operated
54"	48"	42"	50"	42"	34"
1.5"- 4.5"	1.5"- 4.5"	1.5"- 4.5"	1"- 4"	1"- 4"	1"- 4"
7	7	7	7	7	7
Fixed	Fixed	Fixed	Fixed	Fixed	Fixed
11" x 4"	11" x 4"	11" x 4"	11" x 4"	11" x 4"	11" x 4"
20" x 10"	20" x 10"	20" x 8"	18" x 9.5"	18" x 8.5"	18" x 6.5"
					•
Standard	Standard	Standard	Standard	Standard	Standard
Optional High Back w/ Seat Springs,	Optional High Back w/ Seat Springs,	Optional High Back w/ Seat Springs,	N/A High Back w/ Seat Springs	N/A High Back w/ Seat Springs	N/A Mid Back w/ Seat Springs
Lever Adjust & Arm Rests Standard	Lever Adjust & Arm Rests Standard	Lever Adjust & Arm Rests Standard	N/A	N/A	N/A
Stallualu	Stallualu	Stallualu	IV/A	IV/A	IV/A
645	630	615	475	440	425
69"	69"	69"	64"	64"	64"
64"	58"	52"	62"	54"	42"
42"	42"	42"	43"	43"	37"
3 Year Limited Consumer			3 Year Limited Consumer		
5 Year Limited			5 Year Limited		
N/A			N/A		

3-Bucket Powered Bagger Kit, Mulching Kit, Trailer Hitch Kit, 36" Poly Roller, 48" Aerator, 48" Dethatcher, 15-Gallon Sprayer, Spreader, Dump Cart, Wheel Covers, Sun Shade, Headlight Kit, 54" Snow Blade, Two-Stage Snowblower, FlexTend™ Shoulder Support System, Seat Cover, Mower Cover, Engine Guard

2-Bucket Non-Powered Bagger Kit, Mulching Kit, Trailer Hitch Kit (Standard on 42" & 50" models), 36" Poly Roller, 48" Aerator, 48" Dethatcher, 15-Gallon Sprayer, Spreader, Dump Cart, Wheel Covers, FlexTend™ Shoulder Support System, Seat Cover, Mower Cover

PRODUCT NAME	AMP Rider	
MODEL NUMBER	91600200	
MOTORS	Brushless DC Motors	
	4 HP Traction Drive and (2) 1.7 hp Deck	
HORSEPOWER*	Blade Drive	
DRIVE SYSTEM	Hydrostatic Transaxle with 3/4" axles	
BATTERY CAPACITY VOLTS & AMP HOUR RATING	48V 75 AH battery system comprised of (5) 48V 15 AH sub packs.	
GROUND SPEED (APPROX. MPH) (FORWARD/REVERSE)	5 mph/2.5 mph	
RUN TIME (Normal Operation)	50-75 mins.	
CHARGE TIME -5AH CHARGER	12-16 hrs	
CHARGE TIME-20AH CHARGER	4-5 hrs	
DECK		
DECK MATERIAL	12 ga	
DECK CONSTRUCTION	Stamped	
NUMBER OF SPINDLES	2	
BLADE TIP SPEED (FPM)	16,000	
SPINDLE MATERIAL	Steel Motor Shaft	
SPINDLE SHAFT	17 mm Dia. Steel Motor Shaft	
SPINDLE BEARINGS	17 mm Sealed	
DECK DRIVE	2 (1.7 HP) Electric Motors	
DECK ENGAGEMENT	Electric - Blade Mounted Directly to Motor Shaft.	
DECK LIFT SYSTEM	Hand Operated	
CUTTING WIDTH	34"	
CUTTING HEIGHTS	1.5"- 4.5"	
CUTTING POSITIONS	13	
WHEELS		
FRONT AXLE	Floating	
FRONT	11" x 4"	
REAR	18" x 6.5"	
FEATURES	10 X 0.0	
HOOD	Standard	
HEADLIGHTS	N/A	
SEAT	Mid Back w/Seat Springs	
HOUR METER	N/A	
DIMENSIONS	17/1	
WEIGHT (LBS)	530	
LENGTH	61"	
WIDTH	44.5 "	
HEIGHT	41.25 "	
	41.23	
WARRANTY		
WARRANTY (Except Batteries)	3 Year Limited Consumer	
BATTERY WARRANTY	100% first year, pro rated second year	
ATTACHMENTS & ACCESSORIES		
OPTIONAL	48V 20A Charger, Bagger Kit, Mulching Kit	
	1	

PRODUCT NAME	Lawn Tractor 42	Lawn Tractor 46	Garden Tractor 54
MODEL NUMBER	936051	936053	936055
ENGINE	Kohler® Courage Single	Briggs & Stratton® V-Twin	Kohler® Courage V-Twin
HORSEPOWER*	19 hp	22 hp	25 hp
DISPLACEMENT (cc)	597 cc	656 cc	725 cc
DRIVE SYSTEM	Hydrostatic Fender Shift Lever	Hydrostatic Fender Shift Lever	Hydrostatic Foot Pedal
FUEL CAPACITY GALLONS (LITERS)	2.5 Gallons (9.5L)	2.5 Gallons (9.5L)	4.0 Gallons (15.2L)
GROUND SPEED (APPROX. MPH) (FORWARD/REVERSE)	5.5 mph/2.5 mph	5.5 mph/2.5 mph	5.5 mph/2.5 mph
STARTER	Electric (Bendix)	Electric (Bendix)	Electric (Bendix)
DECK			
DECK MATERIAL	12 ga	12 ga	10 ga
DECK CONSTRUCTION	Stamped	Stamped	Stamped
NUMBER OF SPINDLES	2	2	3
BLADE TIP SPEED (FPM)	19,000 (max)	19,000 (max)	19,000 (max)
SPINDLE MATERIAL	Cast Aluminum	Cast Aluminum	Cast Aluminum
SPINDLE SHAFT	Steel	Steel	Steel
SPINDLE BEARINGS	Sealed	Sealed	Greaseable
DECK DRIVE	Belt	Belt	Belt
DECK ENGAGEMENT	PTO Electric	PTO Electric	PTO Electric
DECK LIFT SYSTEM	Manual, Spring Assist	Manual, Spring Assist	Manual, Spring Assist
CUTTING WIDTH	42"	46"	54"
CUTTING HEIGHTS	1.5" - 4"	1.5" - 4"	1.5" - 4"
CUTTING POSITIONS	6	6	7
TURNING RADIUS	16"	16"	18"
WHEELS			
FRONT AXLE	Steel	Steel	Cast Iron
FRONT	15" x 6" - 6" Turf Saver	15" x 6" - 6" Turf Saver	16" x 6.5"- 6" Turf Saver
REAR	20" x 8" - 8" Turf Saver	20" x 8" - 8" Turf Saver	23" x 10.5"- 12" Turf Saver
FEATURES			
HOOD	Stealth	Stealth	Stealth
HEADLIGHTS	Yes	Yes	Yes
SEAT	High Back 15", Slide	High Back 15", Slide	High Back 15", Slide
HOUR METER	Yes	Yes	Yes
DIMENSIONS			
WEIGHT (LBS)	472	493	698
LENGTH	72.75"	72.75"	73.75"
WIDTH	45"	49.5"	58.5"
HEIGHT	46"	46"	47"
WARRANTY			
MACHINE		2 Year Limited Consumer	
ATTACHMENTS & ACCESSORIES			
OPTIONAL		Bagger Kit, Mulching Kit	

PRODUCT NAME	Wide Area Walk 34	Pro21	Classic LM 21	Classic LM21 S	Classic LM21 SW	Value Walk Behind	Value Walk Behind
MODEL NUMBER	911413	911271	911160	911183	911184	961360	961464
ENGINE	Briggs & Stratton®	Kawasaki® FJ180V	Kohler® XT-7	Kawasaki® FJ180V	Kawasaki® FJ180V	Kohler® XT-6	Honda® GCV 160
HORSEPOWER*	14.5 hp	6 hp	4.5 hp	6 hp	6 hp	3.5 hp	5.5 hp
DISPLACEMENT (cc)	500 сс	179 сс	173 cc	179 сс	179 сс	149 сс	160 cc
DRIVE SYSTEM	Variable Speed Belt Drive	Variable Speed Belt Drive	Push	Infi-Speed® Variable Speed Drive	Infi-Speed® Variable Speed Drive	Push	FWD Self Propelled
FUEL CAPACITY Gallons (Liters)	2.5 Gallons (9.5L)	0.53 Gallon (2L)	0.37 Gallon (1.4L)	0.53 Gallon (2L)	0.53 Gallon (2L)	0.24 Gallon (1L)	0.37 Gallon (1.4L)
GROUND SPEED (APPROX. MPH) (FORWARD/REVERSE)	3.5 mph Forward/2 mph Reverse	3.75 mph	N/A	4 mph	4 mph	N/A	N/A
STARTER	Electric Start	Recoil	Recoil	Recoil	Recoil	Manual Pull	Manual Pull
DECK							
DECK MATERIAL	12 ga	14 ga	14 ga	14 ga	14 ga	12 ga	12 ga
DECK CONSTRUCTION	Stamped	Stamped	Stamped	Stamped	Stamped	Stamped	Stamped
NUMBER OF SPINDLES	2	1	1	1	1	1	1
BLADE TIP SPEED (FPM)	17,969	18,000	18,000	18,000	18,000	19,000	19,000
SPINDLE MATERIAL	Steel	Steel	Steel	Steel	Steel	Cast Aluminum	Cast Aluminum
SPINDLE SHAFT	5/8"	7/8"	7/8"	7/8"	7/8"	NA	NA
SPINDLE BEARINGS	Sealed Ball	Sealed Ball	Sealed Ball	Sealed Ball	Sealed Ball	NA	NA
DECK DRIVE	Belt	Direct	Direct	Direct	Direct	NA	NA
DECK ENGAGEMENT	PTO Lever	NA	NA	NA	NA	NA	NA
DECK LIFT SYSTEM	Manual	Manual	Manual	Manual	Manual	Manual	Manual
CUTTING WIDTH	34"	21"	21"	21"	21"	21"	21"
CUTTING HEIGHTS	1.75" - 3.5"	1.5" - 3.6"	1" - 3.25"	1" - 3.25"	1" - 3.25"	1.25" - 3.42"	1.25" - 3.42"
CUTTING POSITIONS	7	6	6	6	6	5	5
WHEELS							
FRONT AXLE	Swivel	Fixed	Fixed	Fixed	Swivel	Fixed	Fixed
FRONT	8"	8"	7.5"	7.5"	7.5"	7"	8"
REAR	13"	8"	10.5"	10.5"	10.5"	12"	8"
DIMENSIONS							
WEIGHT (LBS)	280	125	100	104	121	85	85
LENGTH	67"	62.5"	61.5"	61.5"	61.5"	36.25"	36.25"
WIDTH	42"	23.5"	23"	23"	23"	21"	21"
HEIGHT	38"	40.6"	38"	38"	38"	25.25"	25.25"
WARRANTY							
MACHINE	3 Year Limited Consumer	3 Year Limited Consumer, 1 Year Limited Commercial	3 Year Limited Consumer	3 Year Limited Consumer	3 Year Limited Consumer	2 Year Limited Consumer	2 Year Limited Consumer
ATTACHMENTS & ACCESSORIES							
BAGGER KIT	Available	Standard	Standard	Standard	Standard	Standard	Standard
MULCHING KIT	Available	Standard	Standard	Standard	Standard	Integrated	Integrated
LEAF SHREDDER	N/A	Available	Available	Available	Available	N/A	N/A
DETHATCHER	N/A	N/A	Available	Available	Available	N/A	N/A

PRODUCT NAME	Professional Walk 36GR	Professional Walk 48GR	
MODEL NUMBER	988811	988812	
ENGINE	Kawasaki® FS481V	Kawasaki® FS481V	
HORSEPOWER*	16 hp	16 hp	
DISPLACEMENT (cc)	603 cc	603 cc	
DRIVE SYSTEM	Peerless Gear Drive	Peerless Gear Drive	
FUEL CAPACITY - Gallons (LITERS)	6.6 Gallon (24.9L)	6.6 Gallon (24.9L)	
GROUND SPEED (APPROX. Mph) (Forward/Reverse)	5.4 mph / Reverse Assist	5.4 mph / Reverse Assist	
STARTER	Recoil	Recoil	
DECK			
DECK MATERIAL	7 ga	7 ga	
DECK CONSTRUCTION	Welded	Welded	
NUMBER OF SPINDLES	2	3	
BLADE TIP SPEED (FPM)	18,152	18,220	
SPINDLE HOUSING Material	Aluminum	Aluminum	
SPINDLE SHAFT	1" Steel	1" Steel	
SPINDLE BEARINGS	1" Sealed	1" Sealed	
DECK DRIVE	Belt	Belt	
DECK ENGAGEMENT	Electric Clutch	Electric Clutch	
DECK LIFT SYSTEM	Manual	Manual	
CUTTING WIDTH	36"	48"	
CUTTING HEIGHTS	1.5"- 4"	1.5"- 4"	
CUTTING POSITIONS (1/4" INCREMENTS)	10 10		
WHEELS			
FRONT AXLE	Swivel	Swivel	
FRONT	3.5	3.5	
REAR	6.5	6.5	
DIMENSIONS			
WEIGHT (LBS)	481	548	
LENGTH	75.6"	70.9"	
WIDTH	48.4"	60.8"	
HEIGHT	41.9"	41.9"	
WARRANTY			
MACHINE	2 Year Limited Commercial		
DECK SHELL & FRAME	Limited Lifetime Deck Shell & Frame		
SPINDLES	2 Year Limited Spindle		
	c		
ATTACHMENTS & ACCESSORIE	.5		

PRODUCT NAME	27- Ton Log Splitter	34- Ton Log Splitter	
MODEL NUMBER	917001	917002	
ENGINE	Subaru®	Subaru®	
DISPLACEMENT (cc)	169 cc	211 cc	
STARTING SYSTEM	Recoil	Recoil	
STARTING SYSTEM	.95 Gallon (3.6L)	.95 Gallon (3.6L)	
LOG CAPACITY	25"	25"	
HYDRAULIC CAPACITY	4.5 Gallon(17L)	4.5 Gallon(17L)	
SPLITTING FORCE	27 Ton	34 Ton	
CYLINDER PISTON SIZE	4.5" Bore	5" Bore	
CYLINDER ROD SIZE	1.75"	1.75"	
CYLINDER STROKE	24"	24"	
CYLINDER Construction	Welded -Trunnion Mount	Welded -Trunnion Mount	
RESERVOIR SIZE	3.5 Gallons	3.5 Gallons	
PUMP SIZE	11 GPM	13 GPM	
CYLINDER CYCLE TIME	16 Seconds	18 Seconds	
TIRE SIZE	4.8" / 4" x 8"	4.8" / 4" x 8"	
HITCH COUPLER	2"	2"	
MAX TOWING SPEED	45 mph / 72.4 kmh	45 mph / 72.4 kmh	
MENSIONS			
WEIGHT (LBS)	500	525	
LENGTH (HORIZONTAL Position)	86.25"	86.25"	
LENGTH (Vertical position)	83.75"	83.75"	
WIDTH	38.25"	38.25"	
HEIGHT (HORIZONTAL Position)	46.50"	46.50"	
HEIGHT (Vertical Position)	64.75"	64.75"	
ARRANTY			
MACHINE	3 Year Limited Consumer, 90-Day Limited Commercial	3 Year Limited Consumer, 90-Day Limited Commercial	
ATURES			
SPLITTING Drientation	Vertical or Horizontal		
2-STAGE HYDRAULIC Pump	Yes		
WHEEL FENDERS	Yes		
SAFETY CHAINS	Yes		
LEFT OR RIGHT HAND Operation	Yes		
TACHMENTS & ACCESSOR	IES		
	IES Work Table, Trailer Lights, L		

PRODUCT NAME **MODEL NUMBER ENGINE** HORSEPOWER* DISPLACEMENT (cc) STARTING SYSTEM **FUEL TANK** CAPACITY **BRUSH WIDTH BRUSH ROTATION ANGLE BRUSH ROTATION** CONTROL INTERLOCK CONTROL TIRE SIZE **TIRE TYPE AXLE SYSTEM** SPEEDS: FORWARD/ **REVERSE BRUSH DIAMETER** DIMENSIONS WEIGHT (LBS) LENGTH WIDTH HEIGHT WARRANTY MACHINE **FEATURES ELECTRIC START** HALOGEN **HEADLIGHTS**

ATTACHMENTS & ACCES

OPTIONAL

Power Brush 28	Power Brush 36
921025	926045
Subaru®	Subaru®
6 hp	9 hp
169 cc	265 cc
120V/Recoil	120V/Recoil
.95 Gallon (3.6L)	1.6 Gallon (6.1L)
28"	36"
40°	40°
Remote Trigger	Remote Trigger
Standard	Standard
15 " x 5"	16" x 6.5"
Directional Snow Tread	Directional Snow Tread
Automatic Traction Control	Automatic Traction Control
6 Forward/ 2 Reverse	6 Forward/ 2 Reverse
18"	25"
230	325
65"	72"
34"	44"
44"	43"
3 Year Limited Consumer, 90-Day Limited Commercial	3 Year Limited Consumer, 1 Year Limited Commercial
Stan	dard
N/A	Standard
SORIES	
Snow Cab, Turf	Debris Deflector,

Snow Cab, Turf Wheels, MeltBuddy™

Caster Kit, MeltBuddy™

PRODUCT NAME	Front Tine Tiller	Rear Tine Tiller
MODEL NUMBER	902032	901028
ENGINE	Subaru®	Subaru®
HORSEPOWER*	6 hp	6 hp
ENGINE DISPLACEMENT (cc)	169 cc	169 cc
DRIVE SYSTEM	Roller Chain	Chain / Gear
FUEL CAPACITY Gallons (Liters)	0.89 Gallon (3.4L)	0.89 Gallon (3.4L)
TINE SPEED	118 rpm	190 rpm
STARTER	Pull	Pull
DECK		
TILLING WIDTH	24"/22"/12"	17"
TINE DIAMETER	12"	13"
TILLING DEPTH	6"	6.5"
HANDLE	Foldable	Adjustable
WHEELS		
TIRE SIZE	1.75" x 8" Semi -Pneumatic	13" x 5"- 6" Pneumatic
DIMENSIONS		
WEIGHT (LBS)	115	230
LENGTH (INCHES)	27.5"	48"
WIDTH (INCHES)	25"	24.5"
HEIGHT (INCHES)	33.5"	34.5"
WARRANTY		
MACHINE	2 Year Limited Consumer	2 Year Limited Consumer
FEATURES		
	7 Position, Spring Loaded, Depth and Drag Stake	Dual Rotating Tines, Power Forward and Reverse, Deep Tread Tires

PRODUCT NAME	Lawn Edger	String Trimmer	
MODEL NUMBER	986103	946152	
ENGINE	LCT Overhead Cam	Kohler® XT-7	
HORSEPOWER*	N/A	4.5 hp	
DISPLACEMENT (cc)	136 cc	173 cc	
STARTING SYSTEM	Recoil	Recoil	
DRIVE SYSTEM	Push	Push	
FUEL CAPACITY	0.71 Gallon (2.6L)	0.37 Gallon(1.4L)	
DECK			
DECK MATERIAL	12 ga	14 ga	
DECK CONSTRUCTION	Formed	Stamped	
NUMBER OF SPINDLES	1	1	
BLADE DIAMETER	9 Inch	N/A	
SPINDLE MATERIAL	Steel	N/A	
SPINDLE SHAFT	1/2" Dia. Steel	N/A	
SPINDLE BEARINGS	Sealed	N/A	
DECK DRIVE	Belt	Belt	
CUT ANGLE	110 Degrees	N/A	
CUT POSITIONS	4	4	
CUTTING WIDTH	N/A	22" w/ 15° Swivel to the Left and Right	
CUTTING HEIGHTS	N/A	1.25" - 4.25"	
OPERATOR SAFETY Lever	Yes	N/A	
WHEELS			
WHEEL DIAMETER	8"	N/A	
WHEEL BEARINGS	Yes	N/A	
DROP WHEEL For Curb	Yes	N/A	
FRONT AXLE	Laterally Adjustable	N/A	
FRONT	1.75" x 7.5"	N/A	
REAR	1.75" x 7.5"	14"	
DIMENSIONS			
WEIGHT (LBS)	72	83	
LENGTH	44.75"	58"	
WIDTH	19.75"	22"	
HEIGHT	38"	41"	
WARRANTY			
MACHINE	3 Year Limited Consumer	3 Year Limited Consumer	

BE SURE TO ASK YOUR LOCAL DEALER ABOUT THESE OUTSTANDING ARIENS SNOW PRODUCTS.

THE KING OF SNOW



Durability. Reliability. Unrelenting power. That's what you'll find in the entire Ariens® Sno-Thro® lineup. Every machine is subjected to the most rigorous testing and trial conditions imaginable. So when winter brings on the worst, bring on the best—**The King of Snow**—built to last a lifetime. Consult with your Ariens dealer about selecting the Sno-Thro model that's right for you.

WWW.ARIENS.COM



Phone: 920.756.4688 Email: info@ariens.com